

### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

Trade name Unleaded Petrol 95

Synonyms ULP 95

Relevant identified uses of the substance or mixture and uses advised against

**Use** Fuel for spark ignition powered automotive application.

Manufacturer or supplier's details

Company Sasol Oil Pty (Ltd)

Address Sasol Place, 50 Katherine Street

Sandton 2090

South Africa

Telephone +27860335444

E-mail address sasolchem.info.sa@sasol.com

Emergency telephone number +44 (0)1235 239 670 (Europe, Israel, Africa, Americas)

+44(0)1235 239 671 (Middle East, Arabic African countries)

+65 3158 1074 (Asia Pacific)

+86 10 5100 3039 (China)

+27 (0)17 610 4444 (South Africa)

+61 (2) 8014 4558 (Australia)



### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

### SECTION 2. Hazards identification

#### Classification of the substance or mixture

South Africa. GHS Classification and Labelling of Chemicals - SANS 10234

Classification

Aspiration hazard Category 1
Germ cell mutagenicity Category 1
Carcinogenicity Category 1
Flammable Liquids Category 2

#### Label elements

**Pictogram** 





Signal word Danger

**Hazard statements** H304: May be fatal if swallowed and enters airways.

H340: May cause genetic defects.

H350: May cause cancer.

H225: Highly flammable liquid and vapour.

#### **Precautionary statements**

**Prevention** P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P210: Keep away from heat, hot surfaces, sparks, open flames and

Print Date 12.09.2017 100000003537 2/12



#### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

Response P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER

or doctor/ physician.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water or shower.

P308 + P313: IF exposed or concerned: Get medical advice/ attention.

P370 + P378: In case of fire: Use alcohol-resistant foam, carbon

dioxide or water mist to extinguish. P331: Do not induce vomiting.

Storage P405: Store locked up.

P403 + P235: Store in a well-ventilated place. Keep cool.

**Disposal** P501: Dispose in compliance with local and national regulations.

Other hazards No data available

### SECTION 3. Composition/information on ingredients

**Substance** 

Gasoline, natural; Low boiling point naphtha

**Contents:** 100.00 %W/W

**CAS-No.** 8006-61-9 **Index-No.** 649-261-00-8 **EC-No.** 232-349-1

Print Date 12.09.2017 100000003537 3/12



### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

#### Hazard statements H304 H340 H350 H225

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### SECTION 4. First aid measures

#### Description of necessary first-aid measures

**Inhalation** Move to fresh air in case of accidental inhalation of vapours. If

breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

**Skin contact** Wash off immediately with plenty of water for at least 15

minutes. If skin irritation persists, call a physician.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. If eye irritation

persists, consult a specialist.

**Ingestion** Do not induce vomiting without medical advice. Never give

anything by mouth to an unconscious person. Call a physician

immediately.

Most important symptoms/effects, acute and delayed

Refer to SECTION 11

### **SECTION 5. Firefighting measures**

**Suitable extinguishing** Water spray. Dry powder. Alcohol-resistant foam.

media

Print Date 12.09.2017 **100000003537** 4/12



#### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

Unsuitable extinguishing

Water spray jet.

media

Special hazards arising

Flash back possible over considerable distance. Do not allow

from the substance or

run-off from fire fighting to enter drains or water courses.

mixture

Special protective

In the event of fire, wear self-contained breathing apparatus.

equipment for firefighters

Use personal protective equipment.

#### SECTION 6. Accidental release measures

Personal precautions Keep people away from and upwind of spill/leak. Remove all

sources of ignition. Do not breathe vapours or spray mist.

Environmental precautions Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material and dispose of as

hazardous waste.

Reference to other sections Refer to Section 8 and 13

### SECTION 7. Handling and storage

Safe handling advice Do not breathe vapours or spray mist. Wear personal

protective equipment.

Advice on protection Keep away from open flames, hot surfaces and sources of

**against fire and explosion** ignition. Use explosion-proof equipment.

**Requirements for storage** Keep containers tightly closed in a cool, well-ventilated place.

Print Date 12.09.2017 **100000003537** 5/12



### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

areas and containers

Advice on common storage No data available

### SECTION 8. Exposure controls/personal protection

### Components with workplace control parameters

#### NATIONAL OCCUPATIONAL EXPOSURE LIMITS

No data available

#### **Exposure controls**

#### **Engineering measures**

Provide sufficient air exchange and/or exhaust in work rooms.

#### Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection Impervious gloves

**Eye protection** Safety glasses with side-shields

**Skin and body protection** Safety shoes Protective suit

Hygiene measures Wash hands before breaks and immediately after handling the

product.

### SECTION 9. Physical and chemical properties



#### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

#### Information on basic physical and chemical properties

Form Liquid

State of matter Liquid

Colour green

Odour Hydrocarbon-like

Odour Threshold No data available

pH No data available

Melting point/range -90.5  $^{\circ}$  C

Boiling point/boiling range 38.05 - 215 ° C

Flash point -20 ° C; closed cup

**Evaporation rate** No data available

Flammability (solid, gas) No data available

Auto-ignition temperature 250 ° C

Lower explosion limit 1.3 %(V)

Upper explosion limit 7.1 %(V)

Vapour pressure No data available

Relative vapour density 3

**Density**  $0.710 - 0.785 \text{ g/cm}3; 20 ^{\circ} \text{ C}$ 

Water solubility Immiscible

Partition coefficient: n-

No data available

octanol/water

# SECTION 10. Stability and reactivity



#### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

**Reactivity** Stable under recommended storage conditions.

**Chemical stability** Stable under normal conditions.

Possibility of hazardous

reactions

Heating can release hazardous gases.

Conditions to avoid Heat, flames and sparks. Extremes of temperature and direct

sunlight.

Materials to avoid Oxidizing agents. Acids and bases

Hazardous decomposition

products

Carbon oxides.

### **SECTION 11. Toxicological information**

Acute oral toxicity Gasoline, natural; Low boiling point naphtha:

LD50 Rat: 14,063 mg/kg; (literature value)

**Eye irritation** Gasoline, natural; Low boiling point naphtha:

human: Mild eye irritation (literature value)

### SECTION 12. Ecological information

**Toxicity to fish** Gasoline, natural; Low boiling point naphtha:

static test; Oncorhynchus mykiss; 96 h; LC50; 11 mg/l;

(literature value)

**Toxicity to daphnia and other** Gasoline, natural; Low boiling point naphtha:

aquatic invertebrates static test; Daphnia magna; 48 h; EC50; 12 mg/l(literature

Print Date 12.09.2017 **100000003537** 8/12



### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

value)

# SECTION 13. Disposal considerations

Product Disposal should be in accordance with local, regional and

national legislations.

# **SECTION 14. Transport information**

**ADR** 

UN number: 1203

Class: 3

Packaging group: II; F1;

Proper shipping name: GASOLINE

RID

UN number: 1203

Class: 3

Packaging group: II; F1

Proper shipping name: GASOLINE

**IMDG** 

UN number: 1203



#### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

Class: 3

EmS: F-E, S-E

Packaging group:

Proper shipping name: GASOLINE

ICAO/IATA

UN number: 1203

Class: 3

Packaging group:

Proper shipping name: GASOLINE

# SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

USA TSCA Inventory

All chemical constituents are listed in: USA TSCA Inventory

(See chapter 3)

Canadian Domestic Substances List (DSL) All chemical constituents are listed in: Canadian Domestic

Substances List (DSL) (See chapter 3)

Australian Inv. of Chem. Substances (AICS) All chemical constituents are listed in: Australian Inv. of Chem.

Substances (AICS) (See chapter 3)

New Zealand Inventory of Chemicals

nicals All chemical constituents are listed in: New Zealand Inventory of

(NZIoC) Chemicals (NZIoC) (See chapter 3)

Print Date 12.09.2017 **100000003537** 10/12



#### **Unleaded Petrol 95**

Version 1.00 Revision Date 12.09.2017

Jap. Inv. of Exist. & New Chemicals (ENCS) Components Not listed

Gasoline

Japan. Industrial Safety & Health Law (ISHL) Components Not listed

Gasoline

Korea. Existing Chemicals Inventory (KECI) All chemical constituents are listed in: Korea. Existing

Chemicals Inventory (KECI) (See chapter 3)

Philippines Inventory of Chemicals and

Chemical Substances (PICCS)

All chemical constituents are listed in: Philippines Inventory of Chemicals and Chemical Substances (PICCS) (See chapter 3)

China Inv. Existing Chemical Substances

(IECSC)

All chemical constituents are listed in: China Inv. Existing

Chemical Substances (IECSC) (See chapter 3)

#### SECTION 16. Other information

#### Full text of H-Statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H340 May cause genetic defects.

H350 May cause cancer.

All reasonable efforts were exercised to compile this SDS in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The SDS only provides information regarding the health, safety and environmental hazards at the date of issue, to facilitate the safe receipt, use and handling of this product in the workplace and does not replace any product information or product specifications. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which this product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which this product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place with respect to health and safety.



### **Unleaded Petrol 95**

Version 1.00

Revision Date 12.09.2017

This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of this product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy of, or assume any liability for incomplete information contained herein or any advice given. When this product is sold, risk passes to the purchaser in accordance with the specific terms and conditions of sale.